

MODEL:- UV-PTZ-5036X-CVA

5 million features:

1. 1/3 inch 5 megapixel CMOS sensor;
2. Supports H.265+, H.265, and H.264 encoding
3. Support soft photosensitivity: dual light mode, full color mode, infrared mode;
4. Support intelligent analysis: precise human shape detection, area detection, and trip line detection;
5. Support voice intercom, voice broadcasting, and custom voice; 6. Support image flipping and digital wide motion;
7. Support Onvif;
8. SD Card Supported

Product parameters:

| | |
|----------------------|--|
| MODEL NO | UV-PTZ-5036X-CVA |
| Main control chip | SSC377D |
| image sensor | 5 megapixel, 1/3 "CMOS |
| video processing | H. 265+/H.265/H.264 video encoding, supporting 0.1M-4Mbps adjustable bitstream; Support adjustable frame rate of 1-25 frames/second; |
| Image output | Main stream: 25FPS @ (2592 × 1944/2560 × 1440/2304 × 1296/1920 × 1080/1280 × 720); |
| | Sub stream: D1, VGA, 640 × 360; |
| Audio interface | Audio linear 1 input and 1 output; |
| Audio processing | G. 711 encoding standard, supporting bidirectional voice intercom and audio video synchronization; |
| IR CUT interface | Integrated IRCUT switching circuit, automatic/external control/manual/timed to control IRCUT day and night mode |
| IR Distance | 150Mtr |
| Lens Size | 4.7MM-94MM |
| network interface | 1 RJ45 Ethernet interface, 10/100M adaptive; |
| Lamp board interface | PWM infrared, PWM warmlight; |
| reliability | Comprehensive lightning protection for power supply and network, in accordance with national standard GB/T17626.5 and international standard IEC61000-4-5; |
| Business functions | Support OSD, real-time audio and video transmission, precise human shape detection, dual light source alarm, and audio alarm; |
| Network Protocol | Support network protocols such as HTTP/RTSP/DHCP/NTP/ONVIF |
| source | DC12V power input interface power consumption 120mA |
| work environment | -40~ +65 °C |

| | |
|------|--------------------------|
| size | 38 (length) * 38 (width) |
|------|--------------------------|