

# 3MP 4G Bullet Color Camera

## UV-4GC-TA30T2



### FEATURES

- 3MP (2304 x 1296) Resolution
- All Time Color Vision
- Full Duplex Audio Intercom (Built-in High Sensitivity Mic & Speaker)
- Support 10x Digital Zoom
- Area Motion Detection, Humanoid Detection, Push Realtime Notification on the Application
- Mobile Notification on Human & Motion Detection
- Customized Pre-recorded Voice Alarm
- Support Micro SD Card up to 256GB & Cloud Storage(Optional)
- Compression : H.264 / H.265 / H.265+
- 4G connection. QR code for Easy to add camera in the app
- Monitoring : Mobile/PC Software (TrueCloud)
- Alexa Support



4G  
Network



3MP  
Resolution



Human  
Detection



Works with  
Alexa



256GB  
SD Card



Full-Duplex  
Audio Intercom



All Time  
Color

### TECHNICAL SPECIFICATIONS

<b>Product Code</b>	UV-4GC-TA30T2
Image Sensor	1/2.8" CMOS Sensor
Resolutions	3MP (2304 x 1296)
Lens	4mm
IR LED	9 IR Array
IR Distance	30 Meters
White LED	9 White Array
White LED Distance	20 Meters
Min Illumination	Color : 0.01 Lux, Black & White : 0.001 Lux
Day & Night	IR-cut Auto ICR
Light Mode	Full Color / Infrared / Intelligent
Viewing Angle	Horizontal: 75°, Vertical: 59°, Diagonal: 88°
Video Streaming	Main Stream: 2304x1296@15 fps Sub Stream: 800x448@15 fps
Audio Input / Output	Two way audio, Built in microphone and speakers
Audio Compression Standard	AAC
Zoom	10x Digital
DNR	3D Digital Noise Reduction
White Balance	Auto
WDR	D-WDR
Mirror / Flip	On / Off
Electronic Shutter	Auto
On Screen Display (OSD)	Date, Time, & Title

AI Features	Motion Detection, Human Detection.
Privacy Zone	Support 4 Zone
Monitoring	Android, iOS, Windows (TrueCloud)
Storage	Support Micro SD Card up to 256GB & Cloud Storage(Optional)
Communication Protocol	Private N1/ Rtmp
Connection Mode	4G Sim Network
Slots	4G Sim Card / Micro SD Card
4G Frequency Band	FDD - LTE : B1 / B3 / B5 / B8; TDD - LTE : B34 / B38 / B39 / B40 / B41
Connectors	DC Power Input & Reset Button
Power Input	DC: 12V / 1A (DC 2.1mm Connector)
Power Consumption	≤5W
Working Temperature / Humidity	0-50° C RH Less than 95% (No Condensation)
Storage Temperature / Humidity	-20° C to 60° C / 20% to 90% RH
Housing Type	Plastic
Dimension	141.4mm X 69.8mm X 159mm (H x W x L)
Net Weight	205 Gms
Gross Weight	413 Gms

