

5MP IP COLOR WITH AUDIO

UV-IPC-DA50T2-CA



FEATURES

- 2880 x 1620 Resolution
- All Time Color Vision
- Built-in High Sensitivity Mic
- Power Input : POE 48V Standard/ DC 12V 1Amp
- Support ONVIF protocol
- 4KV lightning protection
- Compression: H.264/H.265/H.264+/H.265+



5MP
Resolution



Human
Detection



256GB
SD Card



All Time
Color



Voice
Prompt



IP66

Technical Specifications

Model No	UV-IPC-DA50T2-CA
Image Sensor	1 / 3" GC4653 CMOS Sensor
Resolution	2880 x 1620
S/N Ratio	> 39.1 dB
Minimum Illumination	Color: 0.1 Lux, B/W: 0.01 Lux
Lens	4 MM
LED	6 Half White LED & 6 Half IR LED
IR LED Range	30 Meters
White LED Range	20 Meters
Light Mode	Full Color / Infrared / Smart
OSD	Date Time & Title
White Balance	Auto
Day & Night	Auto / Color / BW
Noise Reduction	Support 2D / 3D noise reduction
Mirror/Flip	On / Off
Privacy Masking	4 Zone Selectable
Video Streaming	Dual Streaming at the Same Time: H.264 / H264+ / H.265 / H.265+; Main Stream: 2880 x 1620@15fps Sub-Stream:800 x 448@15fps
Audio Streaming	G.711Codec Standard, Support Audio and Video Synchronization
Connectors	Rj45 / DC Input

Power Input	POE RJ45 Input 48V Standard/DC Input 12V – 1A
Power Consumption	≥3W
Lightning Protection	4000V lightning Protection
Operation Temperature / Humidity	-10°C to +50°C / 30% to 80% RH
Storage Temperature / Humidity	-20°C to +60°C / 20% to 90% RH
Housing Type	Plastic IP66
Dimensions	(H)60.6 x (W)61.7 x (L)158.8mm



* Note: Product specifications are subject to change without prior notice.