

**LINKAGE CAMERA SERIES**

**MODEL NO : UV-4GC-TDSLR-303SL-CA**

**3MP + 3MP 4G Solar Linkage Mini PT Camera**  
Faster Speed Increased Capacity



**3MP + 3MP 4G Solar Linkage PT Camera**

**4mm + 4mm Fixed Lens**

**Horizontal Movement Range Pan 270° & Vertical Movement Range Tilt 90°**

**Dual monitoring. One camera for monitoring, One camera for Pan-Tilt monitoring.**

**Built-in high-sensitivity Mic and Speaker, for Full Duplex Audio Intercomm**

**Mobile Notification on Human & Motion Detection**

**Support 10X Digital Zoom**

**Can set 6 preset points favorite locations**

**Support Micro SD Card upto 256GB & Cloud Storage(Optional)**

**Night Vision and Full Color Modes**

**Monitoring: Mobile/PC Software (TrueCloud)**

**4G Connection, QR code camera configuration with mobile/PC**

**Built-in Battery 15600 mAh rechargeable lithium battery with 7 Watt Solar Panel**

## TECHNICAL SPECIFICATIONS

|                                |  |
|--------------------------------|--|
| Product Code                   | : UV-4GC-TDCLR-303SL-CA  |
| Image Sensor                   | : 1/2.8" 3MP+3MP HD CMOS Dual Sensor   |
| Resolutions                    | : 3MP + 3MP (2304 x 2592)  |
| Lens                           | : 4mm + 4mm fixed lens   |
| IR LED                         | : Fixed Camera 2 Array, PT Camera 2 Array                                    |
| IR Distance                    | : 30 Meters  |
| White LED                      | : Fixed Camera 4 White, PT Camera 4 White                                    |
| White LED Distance             | : 30 Meters  |
| Video Compression Standard     | : H.264/H.265/H.265+   |
| Video Streaming                | : Main Stream: 2304 x 2592 / 15 fps<br>: Sub Stream: 800 x 896 /15 fps       |
| Audio Input/Output             | : Two way audio, Built in microphone and speaker                             |
| Audio Compression Standard     | : AAC/G711A  |
| Slots                          | : Nano Sim Card Slot & Micro SD Card Slot                                    |
| Min Illumination               | : Color: 0.01 Lux,Black & White: 0.001 Lux                                   |
| DNR                            | : 3D Digital Noise Reduction   |
| White Balance                  | : Auto   |
| WDR                            | : D-WDR  |
| Mirror/Flip                    | : On / Off   |
| Electronic Shutter             | : Auto   |
| AI Features                    | : Motion Detection, Human Detection  |
| Monitoring                     | : Andriod, iOS, Windows (TrueCloud)  |
| Storage                        | : Support Micro SD Card upto 256GB & Cloud Storage( <i>Optional</i> )        |
| Connection Mode                | : 4G Network   |
| Light Mode                     | : LED Flash; 4G Network not Connected. LED Continue ON; 4G Network Connected |
| Button                         | : Reset Button   |
| Battery                        | : Built-in 15600mAh Rechargeable battery                                     |
| Solar Panel                    | : 7 Watts  |
| Power Input                    | : DC: 5V/2A (Type-C)   |
| Power Consumption              | : ≤ 15W  |
| Thunder Prevention             | : Standard IEC61000-4-5  |
| Working Temperature / Humidity | : -10° C to 50° C / 30% to 80% RH  |
| Storage Temperature / Humidity | : -20° C to 60° C / 20% to 90% RH  |
| Housing Type                   | : Platic (IP66) Housing  |
| Dimension                      | : 130(W)*310(H)*185(L)mm   |
| Net Weight                     | : Gms  |
| Gross Weight                   | : 833 Gms  |

*\*Note: Product Specifications are subject to change without prior notice.*