

# 4MP 4G Solar Mini Pan-Tilt Camera



## FEATURES

- 4MP pan/tilt Smart Mini PT 4G Solar Camera
- Horizontal rotation of 350 degrees, vertical rotation of 90 degrees
- Built-in high-sensitivity MIC and speaker, support two-way audio
- With white light and infrared light, support Two night vision mode : B/W mode, full color mode
- Support human detection. The device can turn on white light when someone into the monitoring area. And the real-time alarm push information is sent on mobile app
- Motion Tracking. When a human figure is detected will be track Automatically
- Built-in Siren. Siren will be trigger when human movement is detected. The voice of the siren can be customized.
- Built-in PIR Sensor
- Built-In Battery 10400mAh Rechargeable lithium battery, With 7W Solar Panel
- Unique With All-Time-Color vision
- Support Micro SD Card Up to 256GB & Cloud Storage (Optional)
- 4G Essecloud, scan the QR code to easily connect the camera
- Support monitoring : PC/Mobile on Essecloud
- IP66 Waterproof Rating, 4000 Lightning Protection
- Compression : H.264 / H.265 / H.265+



4G SIM Support



256GB SD Card



3MP Resolution



Battery Backup



Auto Human Tracking



IP 66 Rating



High Quality Solar Panel



Cloud Recording



Location Presets

## Technical Specifications

<b>Product Code</b>	<b>UV-4GSLR-DA40T2-CA</b>
Image Sensor	1/2.8" CMOS Sensor
Resolution	4MP:2560 x 1440
Video Compression Standard	H.264+ / H.265 / H.265+
Lens	4mm @ F2.0, View angle: Horizontal 88.9° , Vertical 47.5° , 106.3° Diagonal
Infrared LED	4 LED
Infrared IR Distance	30 Meters
White LED	4 LED
White IR Distance	20 Meters
Light Mode	Full color / Infrared
Minimum Illumination	Color : 0.01Lux, Black and White : 0.001 Lux
Video Encode Stream	Main stream : 2304x1296 / 15FPS; Substream: 640x360 / 15FPS
PTZ Rotation Range	Horizontal 350° 0.1°~20°/sec, Vertical 105° 0.1°-20°/sec;
Audio Input / Output	Supports two-way audio, built-in microphone and speaker
Audio Compression Standard	AAC / G711A
WDR	Support DWDR
Electronics Shutter	Auto
4G Frequency Band	FDD-LTE : B1/ B3/ B5/ B8; TDD-LTE : B34/ B38/ B39/ B40/ B41;
PIR Detection	8-10 Meter
Alarm	1) Motion Detection, Alarm Picture Push 2) Human Detection
Monitoring	Android & iPhone / Windows PC (Application Truecloud)

Storage	Support Micro SD card (Max 256G)
Solar Panel	7W
Power Supply	Built-In Rechargeable 18000mAh Battery
Power Input	Type-C DC 5V-2A
Working Temp	0~50°C RH Less than 95% (No condensation)
Storage Temperature/Humidity	-20°C to +60°C / 20% to 90% RH
Housing Type	Plastic [IP66]
Dimension	132 x 191 x 170mm (WxHxL)
Net Weight	0.723kg
Gross Weight	0.978kg

### Similar Products



4G 3MP Solar With Battery Bullet Camera



Solar Panel 12Ah



4G 3MP Dual Lens Mini PT Camera



Smart 4G 3MP Dual Lens Linkage PT Camera



4G 3MP Mini PT Camera



4G 3MP PTZ Camera

\* Note: Product specifications are subject to change without prior notice.



**Technical Support:**

TollFree NO : 8069160400

EMAIL: [info@uniworldvision.com](mailto:info@uniworldvision.com) | [www.uniworldvision.com](http://www.uniworldvision.com)