

4MP IP BULLET CAMERA

UV-IPC-TA40T2-CA-X1

- ▶ 1/3" 4.0 Megapixels Sensor
- ▶ 3.6mm/6mm (optional) Fixed Lens
- ▶ H.265/H.265+ Encoding Formats
- ▶ Inbuilt Audio Mic. Connection
- ▶ Support Onvif, Access Third Party
- ▶ Distance Upto 25m
- ▶ 12V DC , PoE Support



Model	UV-IPC-DA40T2-CA-X1
Camera Type	4 MP Fixed Bullet Camera
Image Sensor	1/4" 4 MP IP Bullet Camera Color with Audio
D/N Switching	Support D/N Switching (IR Cut Optional)
Shutter	1/25 - 1/10000
White Balance	Support Automatic White Balance
Min illumination	0.01 Lux @ F1.6 , AGC ON , 0 Lux With IR
Noise Reduction	Support 3D NR
WDR	Support 3D (WDR)NR
Motion Detection	Support 3D NR
Privacy Shelter	Support 4 Area
Mirror	Mirror
OSD	Support OSD Setting , Drag the Position Freely
Compression	H.265+ / H.265
Resolution	Main Stream : 8.0 MP (3264*2448) , Sub Stream : 448P (800*488)
Frame Rate	25fps (50Hz), 25fps(60Hz)
Ethernet	RJ- 45 10M / 100M
Network Protocol	HTTP , TCP /IP ,IPv4, UPNP , RTSP ,UDP , SMTP ,NTP DHCP , DNCP DNS IP FILTER, PPPOE , DDNS ,FTP, IP SEARCH (Support P6s IP Camera , DVR NVR)
Onboard Storage	Format SD Card , Storage Managment (Built in Slot for SD card)
Input /Output	1 Channel
Power Consumption	POE Support ,DC 12volt Max 6W
Audio	G.711U
Access Protocol	Support Onvif , P6s ,Private Protocol/ CGI



images and the specifications are illustration purpose only may vary



CIN : U72900BR2018PTC037377

www.uniworldvision.com | info@uniworldvision.com

FOR SALES & TECHNICAL SUPPORT

0806-9160-400