

MODEL : **UV-IPC-DA30T2-CA-X1**

3MP IP DOME CAMERA COLOR WITH AUDIO

- 1/3" 3.0 Megapixels Sensor
- 3.6mm/6mm (optional) Fixed Lens
- H.265/H.265+ Encoding Formats
- Inbuilt Audio Mic. Connection
- Support Onvif, Access Third Party
- Distance Upto 25m
- 12V DC , PoE Support



| | |
|-------------------|---|
| Model | UV-IPC-DA30T2-CA-X1 |
| Camera Type | 3 MP Fixed Dome Camera |
| Image Senser | 1/4" 3 MP IP Dome Camera Color with Audio |
| D/N Switching | Support D/N Switching (IR Cut Optional) |
| Shutter | 1/25 - 1/10000 |
| White Balance | Support Automatic White Balance |
| Min illumination | 0.01 Lux @ F1.6 , AGC ON , 0 Lux With IR |
| Noise Reduction | Support 3D NR |
| WDR | Support 3D (WDR)NR |
| Motion Detection | Support 3D NR |
| Privacy Shelter | Support 4 Area |
| Mirror | Mirror |
| OSD | Support OSD Setting , Drag the Position Freely |
| Compression | H.265+ / H.265 |
| Resolution | Main Stream : 8.0 MP (3264*2448) , Sub Stream : 448P (800*488) |
| Frame Rate | 25fps (50Hz), 25fps(60Hz) |
| Ethernet | RJ- 45 10M / 100M |
| Network Protocol | HTTP , TCP /IP ,IPv4, UPNP , RTSP ,UDP , SMTP ,NTP DHCP , DNCP DNS IP FILTER, PPPOE , DDNS ,FTP, IP SEARCH (Support P6s IP Camera , DVR NVR) |
| Onboard Storage | Format SD Card , Storage Managment (Built in Slot for SD card) |
| Input /Output | 1 Channel |
| Power Consumption | POE Support ,DC 12volt Max 6W |
| Audio | G.711U |
| Access Protocol | Support Onvif , P6s ,Private Protocol/ CGI |