

PREMIUM SERIES

MODEL NO: UV-IVR-T110-80M

UNIWORLD PREMIUM 10CH 4K IVR

with Single SATA & 80 Mbps BandwidthZ

UNIWORLD					
			Intelligent Video	Recorder	▲ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓ ↓
H.265 HEVC		SLINK			
HIGH EFFICIENCY VIDEO CODING	ONVIF SUPPORT	SMART LINK	IP MULTIMEDIA SUBSYSTEM (IMS)	APP	144/72 (10ch) 80 Mbps
	*			Ĩ	
TWO WAY AUDIO	HUMAN DETECTION	VEHICLE DETECTION	RETROGRADE	VEHICLE DETECTION	1 SATA UPTO 16TB

INTRODUCTION

10CH intelligent video recorder, support 10CH 4K IP camera input and output. Support IPC smart analysis: Line-crossing detection, Vehicle retrograde, Staff absence, Loitering, Area intrusion, Vehicle illegal parking. Support voice alarm function in various mode. Support modify the light mode of private protocol IPC. Support online upgrade and U disk upgrade our camera, support maximum 1pcs 16TB hard disk, 1 HDMI and 1 VGA output interface, 2 USB port, support mobile phonemonitoring



SPECIFICATION :									
System Structure Embedded LINUX design, pure hard decoding, watchdog, hard disk storage,									
	HDMI HD displa	HDMI HD display, IP network video access.							
Split	1	4	6	8	10				
Decoding	4K	4*1080P	4MP+5*D1	4MP+7*D1	10*D1				
Incoming Bandwidth	80 Mbps								
Video	3840×2160, 19 Support IMS cli	1 HDMI output, 1 VGA output; Resolution: 3840×2160, 1920×1080, 1440×900, 1280×1024, 1280×800, 1024×768 Support IMS client preview; Support mobile APP fast preview Support multi-screen split; 1/2/4/6/8/9/10 screen real-time preview							
Recording Resolution		Support 720P/960P/1080P/3MP/4MP/5MP/4K							
Video Decoding Parameter	NVR synchrono	Support Smart265/H.265/H.264 decoding NVR synchronous playback 4CH (1*4K); IMS client support maximum 4CH remote video playback							
Audio		Standard G.711; Support HDMI audio output, audio output (3.5mm jack), audio input (3.5mm jack), and IMS client audio and video preview and playback							
Storage Managemen	Support timing recording, alarm recording, timing and alarm recording; Alarm recording includes (Motion detection, Human detection, Line-crossing detection, Vehicle retrograde, Staff absence, Loitering, Area intrusion, Vehicle illegal parking)								
	Support extern	Support external USB storage device (such as ordinary U disk, mobile hard disk) backup							
	1 SATA, maximum support 16TB hard disk								
Network Port		1 RJ45 Ethernet port, 10/100M adaptive; Support TCP/IP, IPv4, DHCP, NTP, RTSP, ONVIF, P2P, SMTP, GB28181 ect. network protocol.							
External Port	2 USB2.0 (rear);	Support mouse, USB upgrade, import and export							
User Management	Maximum supp	Maximum support 32 local user							
Front Panel	Support power	, recording, netwo	rk transmission 3 s	tatus indicator					
Buzzer	Support buzzer alarm								
Service Function	Support previe	Support preview, recording, forwarding, and remote service, alarm linkage, and							
	IMS client rem	IMS client remote monitoring software. Support P2P cloud service							
Working Temperature	-10°C ~ +55 °	C							

FOR SALES & TECHNICAL SUPPORT 0806 9160 400



Working Humidity	10%~90%
Power Consumption	≤2W (not with hard disk)
Alarm Port	/
Power	DC +12V/2A
Size (mm)	210*255*42mm(W×L×H)

FEATURES

- Support 10 CH IPC input (8MP/D1+10CH Preview+4CH Playback)
- Support Smart265, H265, H264 decoding format
- Support synchronized recording, remote view, backup recording in MP4 format, mobile view
- Support 10 CH IPC input (8MP/D1+10CH Preview+4CH Playback)
- Support Smart265, H265, H264 decoding format
- Support synchronized recording, remote view, backup recording in MP4 format, mobile view
- Support VGA/HDMI output
- Support preview image and playback image electronic amplification
- Support standard ONVIF, RTSP, GB28181 protocol
- Support RTMP
- Support alarm capture, alarm email sending function
- Support DDNS、UPNP...etc
- Support WEB, mobile view, IMS surveillance
- Support IPC smart analysis: Line-crossing detection, Vehicle retrograde, Staff absence,
- Loitering, Area intrusion, Vehicle illegal parking
- Support channel cruise grouping
- Support network inspection: network traffic monitoring, network diagnosis...etc
- Support maximum 4CH 1080P synchronous playback
- Support fast booting
- New UI interface, smooth operation
- Support 10CH 4K decoding and 4K display output
- Support to add IPC manually or automatically in LAN
- Support to upgrade IPC online and by U disk
- Support to maintain IPC under private protocol, including restore, restart, enable or disable all netcom function
- New optimization, high quality compatibility with hard disk on the market
- Support ANR(Automatic Network Replenishment) function Support select the video stream mode
- Optimize incoming bandwidth up to 80M

** Images are for illustrative purposes only and may not represent the actual product.